

With or without buzzer

Base, tube and
Installation mounting

2 to 5 tier

IP 66 / IP 69k



LED Signal Tower RST 56

686 Signal Tower RST 56

Technical Information

Housing	PC/ABS-Blend
Lens colour/Housing colour	clear/black
Fixing	Base mounting, Tube mounting, Installation mounting M30
Light effects	LED Permanent light
Tone type	Permanent tone (Installation mounting) Multi-tone (Base/Tube mounting)
Operating temperature min./max.	-30°C / +50°C
Protection rating	IP 66/69k



Tube Ø 25 mm, all anodised
Order no.
100 mm long **975 845 10**
250 mm long **975 840 25**
400 mm long **975 840 40**
600 mm long **975 840 60**
800 mm long **975 840 80**
1000 mm long **975 840 03**



Tube Ø 25 mm, all anodised,
45 mm long
Order no. **960 000 31**

Tube with clamp
Order no. **960 000 18**



Base with integrated tube
Order no. **975 840 10**



Fixing bracket M30
Order no. **960 009 32**



Base for tube Ø 25mm,
plastic
Order no. **975 840 90**



Base for tube Ø 25mm,
metal
Order no. **975 840 91**




Foldaway Base
Order no. **960 000 30**



Foldaway Base
Order no. **960 009 12**



Bracket for base mounting with
concealed cable entry
Order no. **960 000 14**



Bracket for tube mounting
Order no. **960 000 01**



Corner fixing bracket
Order no. **960 000 41**

Base / Tube mounting



Dimensions (Ø x H)	57 mm x 156 mm 57 mm x 196 mm 57 mm x 236 mm 57 mm x 276 mm
Tone type	Permanent or Pulse tone adjustable via dip switch
Sound output	82 or 90 dB adjustable via dip switch

Push-in terminals (24V) without buzzer

2 tier	green, red	686 260 05
3 tier	green, yellow, red	686 370 05
4 tier	blue, green, yellow, red	686 480 05
5 tier	white, blue, green, yellow, red	686 590 05

Push-in terminals (24V) with buzzer

2 tier	green, red	686 260 35
3 tier	green, yellow, red	686 370 35
4 tier	blue, green, yellow, red	686 480 35
5 tier	white, blue, green, yellow, red	686 590 35

Installation mounting



Dimensions (Ø x H)	57 mm x 135 mm (Protrusion from panel) 57 mm x 175 mm (Protrusion from panel) 57 mm x 215 mm (Protrusion from panel) 57 mm x 255 mm (Protrusion from panel)
Tone type	Permanent tone
Sound output	90 dB

M12 connector without buzzer

2 tier	green, red	686 263 05
3 tier	green, yellow, red	686 373 05
4 tier	blue, green, yellow, red	686 483 05
5 tier	white, blue, green, yellow, red	686 593 05

M12 connector with buzzer

2 tier	green, red	686 263 15
3 tier	green, yellow, red	686 373 15
4 tier	blue, green, yellow, red	686 483 15
5 tier	white, blue, green, yellow, red	686 593 15

Pre-configured signal tower - Tube mounting



Dimensions (Ø x H)	57 mm x 285 mm
-----------------------	----------------

Push-in terminals (24V) without buzzer

3 tier	green, yellow, red	686 371 05
--------	--------------------	-------------------

Push-in terminals (24V) with buzzer

3 tier	green, yellow, red	686 371 35
--------	--------------------	-------------------



WERMA Signaltechnik GmbH + Co. KG

Dürbheimer Str. 15
D - 78604 Rietheim - Weilheim
Phone + 49 74 24 95 57-0
Fax + 49 74 24 95 57-44
www.werma.com
info@werma.com

WERMA Signaltechnik

Niederlassung Neuhausen am Rhf.
Rheingoldstrasse 50
8212 Neuhausen am Rheinfall
Switzerland
Phone + 41 52 674 00 60
Fax + 41 52 674 00 66
www.werma.com
info@werma.ch

WERMA Italia S.r.l.

Via dell'Artigianato 42
29122 Piacenza
Italy
Phone + 39 05 23 04 45 44
www.werma.com
info@werma.it

WERMA SARL

56, Rue Colière
69780 Mions
France
Phone + 33 4 72 22 37 37
www.werma.com
info@werma.fr

WERMA BENELUX

Poortakkerstraat 41C
9051 Sint-Denijs-Westrem
Belgium
Phone + 32 9 220 31 11
www.werma.com
info@werma-benelux.com

WERMA (UK) Ltd.

11 Regent Park
37 Booth Drive
Park Farm Industrial Estate
Wellingborough NN8 6GR
Great Britain
Phone + 44 15 36 48 69 30
Fax + 44 15 36 51 48 10
www.werma.com
uksales@werma.co.uk

WERMA USA Inc.

1266 Oakbrook Drive, Suite A
Norcross, GA 30093 USA
Phone + 1 470 361 0600
www.werma.com
us-info@werma.com

WERMA (Shanghai) Co., Ltd.

Building 8, No. 85, Mingnan Road,
Songjiang, Shanghai, P. R. C
201613
China
Phone + 86 21 57 74-0022
Fax + 86 21 57 74-6601
www.werma.com.cn
info@werma.com.cn